



Hilomast Internal Cable Option

No More Nycoils!

Coiled internal cable now available for the following masts:

Mast	Height Extended	Height Retracted	Number Of Sections	Diameter Of Top Section	Diameter Of Base Section	Vertical Headload	Max. Wind Speed Unguyed	Max. Wind Speed With Top Guys	Basic Weight Of Mast
	(ft)	(ft)		(inches)	(inches)	(lbs)	(mph)	(mph)	(lbs)
NK 6	19' 4"	5' 5"	5	2	4	59	101	101	46
NK 9	29' 6"	7' 6"	5	2	4	48	70	85	57
NK 16	52' 6"	13' 1"	5	2	4	44	40	69	97
NL 8	25' 11"	5' 10"	7	2	5	55	87	87	74
NL 9	28' 10"	8' 0"	5	3	5	77	80	80	81
NL 16	51' 2"	13' 7"	5	2.5	5	50	48	63	134
NX 8	24' 11"	6' 4"	7	3	6	110	96	96	110
NX 10	33' 1"	8' 3"	6	3.5	6	110	74	74	132
NY 7	22' 0"	5' 4"†	7	4.5	9.37	264	93	*	194
BR 25	25' 0"	6'	6	3.5	6	150	91	*	110
BR 30	30' 0"	7'	6	3.5	6	110	74.5	*	120

Benefits

- Optional 12 x 0.5mm core screened cable
- Tidier/less hazardous deployment
- No Nycoil or Nycoil basket
- No coiled cable
- No external guides
- No snagging

